

DRD

Submersible sewage electric pumps in cast iron with multi-channel impeller

Three phase 400V

Model	Code	£ Stg	HP	kW	rpm	Abs. Curr. [A] 400V	Passage [mm]	DNM	Weight [kg]
65DRD53.1T2CG **	1875000225	2732	4,2	3,1	2803	5,8	30	65	61,0
65DRD53.6T2BG **	1875000224	2732	4,8	3,6	2822	6,6	30	65	62,0
80DRD55T2BG *	1875000227	3666	6,7	5	2842	9,1	30	80	73,0
80DRD56T2AG *	1875000226	3666	8	6	2842	10,9	30	80	75,0
80DRD57.5T2AG *	1875000228	6671	10,1	7,5	2842	13,5	30	80	150,0
100DRD52.7T6AG **	1875000243	4209	3,6	2,7	931	5,8	80	100	96,0
100DRD52.8T6AG *	1875000244	4728	3,8	2,8	931	6	80	100	114,0
100DRD54.6T4CG *	1875000238	4547	6,2	4,6	1401	9,3	80	100	115,0
100DRD54.6T4BG *	1875000237	4547	6,2	4,6	1401	9,3	80	100	115,0
100DRD57.5T4FG *	1875000240	6076	10,1	7,5	1436	14,3	80	100	175,0
100DRD510T4FG *	1875000242	8860	13,4	10	1436	19	80	100	205,0
100DRD510T4AG *	1875000241	8860	13,4	10	1436	19	80	100	200,0
100DRD512T2DG *	1875000232	9765	16,1	12	2852	21,7	40	100	200,0
100DRD514.9T2CG *	1875000231	9765	20	14,9	2881	26,8	40	100	195,0
100DRD516.6T2BG *	1875000230	9922	22,3	16,6	2881	29,8	40	100	205,0
100DRD520T2AG *	1875000233	14682	26,8	20	2891	35,8	40	100	340,0
100DRD518.2T2AG *	1875000229	9922	24,4	18,2	2891	32,6	40	100	206,0
150DRD56T6CG *	1875000245	8039	8	6	941	12	80	150	190,0
150DRD58T6BG *	1875000246	9786	10,7	8	941	15,8	80	150	220,0
150DRD512T6AG *	1875000248	13600	16,1	12	951	22,9	100	150	382,0
150DRD514T6BG *	1875000249	13600	18,8	14	956	26,2	100	150	375,0
150DRD523T4CG *	1875000253	15865	30,8	23	1441	42,2	100	150	430,0
150DRD527T4BG *	1875000252	15865	36,2	27	1441	49,6	100	150	430,0
150DRD530T4BG *	1875000257	17845	40,2	30	1450	54,3	100	150	518,0
150DRD535T2AG *	1875000236	24830	46,9	35	2901	61,8	50	150	512,0
150DRD535.7T4EG *	1875000258	17752	47,9	35,7	1450	63,6	100	150	518,0
150DRD540.2T2BG *	1875000234	23426	53,9	40,2	2901	71	50	150	500,0
150DRD541T4AG *	1875000256	25108	55	41	1450	73,1	100	150	518,0
150DRD552T2CG *	1875000235	24830	69,7	52	2911	90,1	50	150	495,0
150DRD560T4GG *	1875000263	33767	80,5	60	1455	101,3	60	150	745,0
150DRD575T4CG *	1875000266	50235	100,6	75	1455	126,3	60	150	915,0
150DRD580T4BG *	1875000265	50235	107,3	80	1455	134,8	60	150	915,0
150DRD580T4AG *	1875000264	50235	107,3	80	1455	134,8	60	150	915,0

Tripod or lowering device required for all models

Product available in different materials and voltages, for more information please contact the sales network

* Three phase 400/690V - DOL-SD start

** Three phase 400V - DOL-SD start

DRD

Submersible sewage electric pumps in cast iron with multi-channel impeller

Three phase 400V

Model	Code	£ Stg	HP	kW	rpm	Abs. Curr. [A] 400V	Passage [mm]	DNM	Weight [kg]
200DRD56.2T8CG *	1875000284	POA	8,3	6,2	706	14,4	102	200	330,0
200DRD58T8AG *	1875000285	POA	10,7	8	715	17,1	102	200	330,0
200DRD56T8AG *	1875000286	POA	8	6	706	13,9	102	200	430,0
200DRD59.8T6CG *	1875000247	POA	13,1	9,8	941	19,3	102	200	332,0
200DRD59.3T8CG *	1875000288	POA	12,5	9,3	715	19,8	102	200	430,0
200DRD59.3T8BG *	1875000287	POA	12,5	9,3	715	19,8	102	200	435,0
200DRD515.8T6CG *	1875000275	POA	21,2	15,8	956	29,6	102	200	460,0
200DRD514T6BG *	1545000713	POA	18,8	14	956	26,2	102	200	385,0
200DRD514T6AG *	1875000272	POA	18,8	14	956	26,2	102	200	382,0
200DRD518.9T6BG	1875000274	POA	25,3	18,9	956	34,8	102	200	460,0
200DRD523T6AG *	1875000273	POA	30,8	23	960	40,6	102	200	460,0
200DRD540T4CG *	1875000262	POA	53,6	40	1450	71,3	102	200	665,0
200DRD544T4BG *	1875000261	POA	59	44	1445	78,1	102	200	665,0
200DRD548T4AG *	1875000260	POA	64,4	48	1455	85,2	102	200	665,0
250DRD515T4AG *	1875000259	POA	20,1	15	1441	27,8	73	250	440,0
250DRD512.4T8DG	1875000289	POA	16,6	12,4	715	26,5	105	250	520,0
250DRD517.1T8CG	1875000291	POA	22,9	17,1	715	35,1	105	250	520,0
250DRD519T8AG *	1875000290	POA	25,5	19	715	39	105	250	600,0
250DRD523T6DG *	1875000276	POA	30,8	23	960	40,6	105	250	530,0
250DRD529T6CG *	1875000277	POA	38,9	29	960	52,8	105	250	590,0
250DRD539.2T6BG	1875000279	POA	52,6	39,2	965	71	105	250	750,0
250DRD539.2T6AG	1875000278	POA	52,6	39,2	965	71	105	250	750,0
250DRD565T4DG *	1875000270	POA	87,2	65	1455	109,7	105	250	940,0
250DRD575T4CG *	1875000269	POA	100,6	75	1455	126,3	105	250	970,0
250DRD575T4BG *	1875000268	POA	100,6	75	1455	126,3	105	250	940,0
250DRD585T4AG *	1875000267	POA	114	85	1455	143,2	105	250	940,0
300DRD521.8T8BG	1875000292	POA	29,2	21,8	720	43,7	50X140	300	1024,0
300DRD526.7T8CG	1875000293	POA	35,8	26,7	720	53,5	50X140	300	1024,0
300DRD533.4T6DG	1875000281	POA	44,8	33,4	960	60,8	50X140	300	1030,0
300DRD539.2T6CG	1875000280	POA	52,6	39,2	965	71	50X140	300	1030,0
300DRD555.8T6BG	1875000283	POA	74,8	55,8	965	99	50X140	300	1190,0
300DRD565T6AG *	1875000282	POA	87,2	65	965	115,3	50X140	300	1190,0
350DRD545T8AG *	1875000294	POA	60	45	725	88,3	112	350	1350,0
350DRD540T8CG *	1875000295	POA	53,6	40	720	79,3	112	350	1350,0

Tripod or lowering device required for all models

Product available in different materials and voltages, for more information please contact the sales network

* Three phase 400/690V - DOL-SD start